



# ENI PoC #11: Intelligent Energy Management of DC

Rapporteur: (China Telecom)

Yu Zeng, Hongdan Ren, Ziting Zhang, Yannan Bai, Xu Dan

Co-Rapporteur:

Haining Wang (Intel), Da Wang(Asiainfo), Yue Wang(Samsung), Aldo Artigiani (Huawei)



#### **PoC** member, tasks and goals

#### **Host/Team Leader**:




#### **Team members:**











- PoC Project Goal #1: DC profile analysis. Demonstrate the use of AI-based methods to analyze energy related data, e.g. DC dynamic environment and IT workload data etc..
- ✓ **PoC Project Goal #2:** Policy-based, model-driven DC Energy Management. Demonstrate the use of AI algorithms to enable policy-based and model-driven energy management..

© ETSI 2021




#### PoC Motivations: globally, many countries promised to zero carbon emissions (ZCM) by 2050

Currently, data centers around the world consume about 200TWh of electricity per year, accounting for about 1% of global electricity consumption. It is expected that data centers around the world will consume 20% of global electricity by 2025.

In order to actively deal with global climate change, 30 countries have started the process of moving towards ZCM and decided to ZCM before 2050. It is imperative for global DC to save energy and reduce emissions.

Industries are heavy on electricity bills. The space for traditional energy saving method is limited, which cannot match the energy saving demands for diversified business ecology towards 5G. Hence, intelligent energy saving of DC plays an overall and key role 151 2021





#### **China Telecom Facts\*:**


#### **China Telecom IDC**

- > Largest service provider in China
- > Mainstream internet ecosystem support

#### **Connecting over 300 cities**

> IDC Site: 700+ (large scale)

Rack No.: 420K+Bandwidth: 300T+



\*Data taken from Deloitte 2020 China Telecom annual report




#### **Traditional IDC power saving reached ceiling**

#### **Challenges**

- > High energy consumption
- > IT load(50%), cooling(30%+), lighting etc.
- > 5G edge DC number increasing


#### **Traditional IDC power saving**

- > CFD optimization
- > Temperature tunning
- Power off low load equipment
- > Electricity bill discount
- Natural cooling











**CFD** 






#### **IDC Energy Management Platform online (V3)**











#### **Architecture of PoC System**





#### **Control Flow of PoC System**





#### Test Report from **CAICT** 中国信通院

| NO. | Test Object              | Test Result | Date      |
|-----|--------------------------|-------------|-----------|
| 1   | PUE before system launch | 1.373       | 2020.4.29 |
| 2   | PUE after system launch  | 1.352 🔻     | 2020.4.30 |

| A list of the tested equipment and the test contents |              |               |                |                  |  |  |  |  |
|--|--------------|---------------|----------------|------------------|--|--|--|--|
| Equipment name: DC energy saving platform            |              |               |                |                  |  |  |  |  |
|  | Test<br>item | Measured item | Qualified item | Unqualified item |  |  |  |  |
| Test content:  |              |               |                |                  |  |  |  |  |
| 1、Cloud platform                                     | 8            | 8             | 8              | 0                |  |  |  |  |
| 2、Edge system  | 4            | 4             | 4              | 0                |  |  |  |  |
| 3. Data processing and synchronization               | 3            | 3             | 3              | 0                |  |  |  |  |
| Total  | 15           | 15            | 15             | 0                |  |  |  |  |

100%qualified



#### **PoC System Logic**

#### Step 1


Basic data of IDC room

**Temperature Data** 

Real-time data of the cabinet

Real-time data of air conditioning

Equipment parameter data



#### Step 2



Data analysis & presentation



Release Policy



Cloud&Edge collaborative processing





Automatic Control

- a) Deploy the cloud system
- b) Deploy the Edge system
- c) Joint debugging and testing of the Cloud & Edge system
- d) Joint debugging and testing of the Cloud & IDC system




#### **Data Flow of PoC System**








#### Al modeling process



© ETSI 2021



#### **Al Energy Saving Overview**



© ETSI 2021



#### **Examples of AI algorithm models**

#### Prediction Model for Water-cooled IDC Power Consumption


#### Input

- Chilled water supply pressure
- **②** Frozen return water flow
- Chilled water supply temperature


- **4** Frozen return water temperature
- **⑤** Outdoor temperature
- 6 Outdoor humidity

#### Output

Water cooling unit power







The relationship curve between the main air conditioning engine power consumption (vertical axis) and the chilled water temperature (horizontal axis) with constant parameters




#### **Calculation method of power saving**

**PUE** = Total Facility Power of IDC/ IT equipment energy consumption

= (IT equipment energy consumption + Air conditioning refrigeration energy consumption) /IT equipment energy consumption

**Power Saving** = Air conditioning refrigeration power consumption in non-energy saving state – Air conditioning refrigeration power consumption in energy-saving state

#### **Practical Effect of Poc Project**





#### **Use Case on Al Policy**

#### **Brief Intro**

Based on phase I results, the remaining 11 DC room of building 2, the PID value adjusted based on cold aisle temperature, change end air-con that below 23 degree, thus increase room temperature

■ **data:** 2021.4.23 to 6.6.T0 2021.6.7to6.9T1;

■ No.of Room: 11个 network DC;

■ Fan Motor Adjusted:101;

**■ Temp. Adjusted** 25;

**■ Power Off Air Condition** 6

#### Al based policy settings

|               | Fan Power Range |         |         |         |         |         |          | Temperature |   |
|---------------|-----------------|---------|---------|---------|---------|---------|----------|-------------|---|
| Original      | 40%-80%         |         |         |         |         |         |          | 22°C±1°C    |   |
| New           | 40%-60%         | 50%-70% | 40%-70% | 50%-80% | 60%-80% | 70%-80% | 24°C±1°C | 25°C±1°C    |   |
| Value Changed | 25              | 59      | 1       | 6       | 1       | 2       | 18       | 6           | 6 |
| Room 1-1      | 3               | 5       |         |         |         |         | 4        | 2           |   |
| Room 1-2      | 3               | 3       | 1       | 1       |         |         | 2        | 2           | 1 |
| Room 1-3      | 3               | 6       |         |         |         | 2       | 1        | 1           |   |
| Room 1-4      | 4               | 2       |         | 1       | 1       |         | 1        |             | 2 |
| Room 1-5      | 4               | 6       |         |         |         |         | 3        | 1           |   |
| Room 1-6      | 1               | 8       |         | 1       |         |         | 2        |             |   |
| Room 1-7      |                 | 12      |         |         |         |         | 2        |             |   |
| Room 1-8      |                 | 8       |         |         |         |         | 1        |             |   |
| Room 1-9      | 2               | 3       |         | 3       |         |         |          |             | 3 |
| Room 1-10     | 4               | 1       |         |         |         |         | 2        |             |   |
| Room 1-11     | 1               | 5       |         |         |         |         |          |             |   |
| Total         | 25              | 59      | 1       | 6       | 1       | 2       | 18       | 6           | 6 |




#### **Use Case on Al Policy**

#### **Phase II Results**


Applying AI policy to IDC for 14 days:


- End Air Condition Energy Saving Rate 32.1%;
- DC Room Energy Saving Rate2.8%;
- 14 days Electricity Saving 25070.71kW; Year forecast 65.36
   Million kWh
- 14 days Electricity Bill saving 13788.89 RMB; Year forecast 35.95 Million RMB (0.55RMB/kWh);


# Air Con. Daily Energy Consumption 800.00 700.00 600.00 500.00 200.00 100.00 27.5% 55.3% 18.0% 69.5% 12.7% 34.1% 19.9% 40.5% 37.5% 9.0% 47.0% 100.00 2.5! 2.6! 3.1. 3.2 3.3! 3.4! 3.5! 3.6! 4.4 4.5! 4.6!



#### **Highest Saving achieved:**









#### **Use Case on Al Policy**

#### **Brief Intro**

Based on basic data, temperature data, real-time data of the cabinet, real-time data of air conditioning, change the equipment setting

■ **data:** T0-2021.6.15 to 6.22 T1-2021.6.25 to 6.30;

■ Fan Motor Adjusted: 5;

■ Temp. Adjusted: 27;


■ Power Off Air Condition: 0

#### **Comparison of effect before and after Policy Implementation**

| Room 2-3                                 | 2020/6/22 | 2020/6/23 | 2020/6/24 | 2020/6/25 | 2020/6/26 | 2020/6/27   | 2020/6/28 | 2020/6/29 | 2020/6/30 |
|--|-----------|-----------|-----------|-----------|-----------|---|-----------|-----------|-----------|
| B 0 0 14 4                               | 655.9     | 649.2     | 654.1     | 658.5     | 642.2     | 671.5   | 654.3     | 653.3     | 654       |
| Room 2-3 Line A                          | 648.8     | 646.1     | 648.9     | 653.5     | 639       | 664.5   | 648.6     | 648       | 648.9     |
| Room 2-3 Line B                          | 508.9     | 505.8     | 508.2     | 509.2     | 502.9     | 515.4   | 504.5     | 504.7     | 507.8     |
| ROOM 2-3 Line B                          | 521.6     | 518.3     | 521       | 521.5     | 515.7     | 526.9   | 516       | 516.4     | 520.1     |
| Room 2-3 Line C                          | 659.6     | 665.7     | 660.9     | 660.7     | 665.4     | 658.6   | 659.5     | 660.2     | 661       |
| ROOM 2-3 Line C                          | 595.2     | 605.9     | 597.4     | 596.7     | 606.5     | 591.1   | 597.2     | 594.3     | 597.5     |
| Room 2-3 Line D                          | 308.5     | 496.1     | 403.5     | 408.1     | 493.2     | 327.2   | 407.2     | 410.9     | 408.4     |
| ROOM 2 5 Line b                          | 320.1     | 486.9     | 396.6     | 397.3     | 482.2     | 322.4   | 411.6     | 401.8     | 403.9     |
| Room 2-3 Line E                          | 434.1     | 434.4     | 433.5     | 433.1     | 432.8     | 438.2   | 433.4     | 433.1     | 432.3     |
| ROOM 2 5 Line E                          | 439.4     | 439.4     | 438.6     | 438.3     | 437.3     | 591.1         597.2         594.3         597.5           327.2         407.2         410.9         408.4           322.4         411.6         401.8         403.9           438.2         433.4         433.1         432.3           443.9         438.5         438.2         437.4           373.5         366.8         365.6         365.9           359.9         353         351.6         351.9           196.8         193.2         194.6         194.8           446.9         445.7         447.3         447.7 | 437.4     |           |           |
| Room 2-3 Line F                          | 364       | 363.8     | 363.8     | 365.6     | 361       | 373.5   | 366.8     |           | 365.9     |
| ROOM 2 5 Line i                          | 350.1     | 349.4     | 349.9     | 351.7     | 346.5     | 359.9   | 353       | 351.6     | 351.9     |
| Room 2-3 Line G                          | 200.6     | 191       | 195.3     | 193.9     | 190.3     | 196.8   | 193.2     | 194.6     | 194.8     |
|  | 438.2     | 452.2     | 445.8     | 445.4     | 446.9     | 446.9   | 445.7     | 447.3     | 447.7     |
| Total IT Equipment Power Consumption     | 6445      | 6804.2    | 6617.5    | 6633.5    | 6761.9    | 6536.8  | 6629.5    | 6620      | 6631.6    |
| Total Air Conditioner Energy Consumption | 535       | 509       | 416       | 365       | 384       | 376   | 386       | 388       | 396       |
| Policy Execution Time                    |           |           |           |           |           |   |           |           |           |
| PUE                                      | 1.08      | 1.07      | 1.06      | 1.06      | 1.06      | 1.06  | 1.06      | 1.06      | 1.06      |
| PUE before executing the policy          |           |           |           |           | 1. 08     |   |           |           |           |
| Saving electricity quantity              |           |           | 123. 33   | 175. 63   | 167.10    | 156. 75   | 154. 31   | 151.53    | 144. 48   |
| Refrigeration energy saving rate         | 30. 33%   |           |           |           |           |   |           |           |           |
| Total energy saving rate                 | 2. 25%    |           |           |           |           |   |           |           |           |



#### **Poc#11 Achievement Display**






#### Intel DCM – IT load analysis



Intel DCM software installed in CT lab, and IT load information can be obtained



IT load and server status (e.g. CPU frequency etc.) can be analyzed on a defined frequency




22

#### ENI PoC project #11: Intelligent Energy Management of DC

#### Intel® DCM Overview

- Intel® DCM is an out-of-band software solution for monitoring and managing the inventory, utilization, health, power, and thermals of servers and other IT devices.
- Intel DCM reduces data center total cost of ownership (TCO) by:
  - Improving inventory & asset management
  - Increasing data center reliability
  - Simplifying maintenance
  - Optimizing power & cooling efficiency
  - Maximizing compute density
  - Reducing downtime




DCM Instance, devices being monitored, and users are on the same network

© ETSI 2018



#### Intel® DCM Software Architecture



#### Scales to 10Ks of nodes

iDRAC = Integrated Dell Remote Access Controller CMC = Chassis Management Controller CLI = Command Line Interface DCMI = Data Center Manageability Interface



#### Intel® DCM Use Cases

#### **Capacity Planning**

- Where to place devices
- Optimizing rack density
- Keeping up and forecasting power, space, and processing demands

#### **Health Monitoring**

- Realtime issue detection
- Locating hotspots
- Predicting health issues
- Reliable & customizable alerts

# **Infrastructure and Asset Management**

- Discovering and tracking assets
- Knowing details of available systems
- Building visual layouts and maps
- Aggregating info for the entire infrastructure

#### **Manageability**

- Remote control
- Identifying component issues
- Updating firmware
- Provisioning systems

#### **Utilization Monitoring**


- Monitoring utilization
- Identifying unused devices
- Application & workload optimization
- Network monitoring

#### **Energy Consumption**

- Over-provisioning power and cooling
- Granular thermal mapping
- Monitoring energy use per device
- Power Capping




#### Intel CPU Frequency Tuning Approach



P<sub>t</sub>: Set of CPU platform telemetry features

*C*<sub>t</sub>: Current system status, e.g., CPU core frequencies

 $b_t$ : Traffic bandwidth at time t



Saving 30~40% of power consumption




### **Dynamic Frequency Tuning with Traffic Change**






#### **Power Saving for NFV/5G Core Functions in DC**





#### Power control technology (Out-of-band)



#### **Problem statement**

- Need to ensure the HPC cluster power consumption stays within allowed limits
- Power saving when HPC cluster is not fully loaded



#### Power control on the Node and Cluster level

- Easily control power of defined groups of servers
- Cross vendors



#### **Values**

- Power cap at the cluster makes sure cluster doesn't exceed allowed limit
- Power cap servers during low utilization times = **Power Saving**



#### **PoC Milestones and Current Progress**

**Target** 

Current

| PoC Milestone | Stages/Milestone description | Target Date    | Additional Info                       |
|---------------|------------------------------|----------------|---------------------------------------|
| P.S           | PoC project submission       | 03/2020        | Presentation during #ENI 13           |
| P.TP.1        | PoC Test Plan 1              | 12/2020        | Initial testbed up and running        |
| P.D1          | PoC Demo 1                   | 04/2021        | Demo at Big Data Expo Kunming 2001    |
| P.D2          | PoC Demo 2                   | 06/2021        | Internal demo at ENI#18               |
| P.D3          | PoC Demo 3                   | 07/2102        | ENI webinar demo (27th July)          |
| P.C1          | PoC Expected Contribution 1  | 07/2021        | Contributions to ENI use case         |
| P.C2          | PoC Expected Contribution 2  | 07/2021        | Contributions to ENI requirement      |
| P.C3          | PoC Expected Contribution 4  | 09/2021        | Contributions to ENI terminology      |
| P.C4          | PoC Expected Contribution 5  | 09/2021        | Contributions to ENI data mechanism   |
| P.R           | PoC Report                   | 09/2021        | PoC-Project-End Feedback              |
| P.E           | PoC Project End              | 12/2021        | Presented to ISG ENI for information  |
|               | Note: The deadlines may      | subject to cha | ange according to covid-19 situation. |



**PoC Demos** 

## PoC#11 demonstrated at "eDC" launch on 20<sup>th</sup> Oct. 2020 Beijing together with Intel and Huawei



# MWC Shanghai 2021, Huawei demonstrated 'zero emission network 'including IDCs



© ETSI 2021



#### **PoC Impact**

AllA Alliance Proposal on "IDC Carbon Emission Estimate " 6-8 July 2021, supported by China Mobile and China Unicom







#### **China Telecom Annual Report – Key Business Impact**





#### **Industry Alliance on IDC energy management**





#### **PoC Impact**

CCSA 18<sup>th</sup> meeting 3<sup>rd</sup> Prize on Network Intelligence 25<sup>th</sup> April 2021



China Telecom, Intel, Huawei

Big Data Expo, New Product Award on «Al Based Intelligent Energy Operation System» 2021 26<sup>th</sup> May, Kunming



**China Telecom IDC team** 

© ETSI 2021




#### **PoC Impact**

# **Applied The Network Transformation Awards 2021** in SDN NFV World Congress 2021 October by Layer123



#### 1 - 5G Service Excellence





#### **Key PoC team members**



